

AVD008R

8" Industrial LCD monitor



Specifications

Display

- LED Size: 8" 4:3
- Resolution: 1024 x 768
- Brightness: 300 cd/m²
- Contrast Ratio: 800:1
- Colors: 16.7 M
- Viewing Angle (H/V°): 75 / 75
- Backlight: LED
- Backlight MTBF (hrs): 50000
- Response Time: 5 ms

Touch Screen

- 10 points Resistive Multi-touch, USB/RJ45 interface

OSD Function

- OSD keys on rear side

Audio

- Line in 3.5 mm jack, Speakers

Rear I/O

- 1x DVI-D
- 1x VGA
- 1x HDMI
- 1x DP
- 1x USB
- Power input terminal block
- Power input DC Jack

Power Supply

- Power input: +12~+36V DC

Mechanical

- Aluminium Alloy
- IP front protection: IP65
- Mounting: Wall mount VESA 75x 75 / 100x100 mm

Dimensions

- Dimension (W x H x D mm): 223 x 182.5 x 43 mm
- Cut out: 211.3 x 170.8 mm
- Weight: 2.1 kg Net / 3.2 kg Gross

System & Environment

- Operating temperature: -20°C to 70°C
- Operating humidity: 10% to 80%
- Storage temperature: -20°C to 70°C
- Storage humidity: 10% to 90%

Certifications

- CE

Ordering Information

- AVD008R (P/N: 57651700)
Industrial 8" LCD monitor, 1024x768 XGA, 400 cd/m², resistive touch screen, IP65 front, VGA, DVI, HDMI, USB/RJ-45, Audio ports, speakers, DC terminal block 12-36V DC-in, DC Jack, power adapter, 6x panel mount holes

Package Contents:

- 1x VGA Cable D-SUB 15-pin
- 1x USB Touch Cable
- 1 x Power Cord
- 1 x Power Adapter
- 8 x Mounting Clips