

PRIME PANEL TOUCH ATTACHMENT 15.6" / 21.5"

FACT SHEET

MULTITOUCH MONITOR FOR DEMANDING TASKS

- High operational reliability through robust system design and IP65
- Safe operation due to good readability and precise touch sensor



Housing

High quality aluminum housing.
Modern design, "form follows function".
Optional with logo and color ident.



Glass Front


Anti-reflective and hardened - optimal readability,
reduced reflections, high scratch resistance.
Easy to clean.



Touch

High operational safety - even under disturbing influence.
EMC-stable 4-finger operation, glove operation (cat. 1)
pre-parameterized.
Optional specific parameterization for palm suppression
or working gloves.

THE MODULAR SYSTEM PRIME CUBE®



Modular

Customized solutions of industrial computer technology with
all advantages of standard products: Validated platforms, short
development process, optimum price-performance ratio.



High Quality

For 24/7 operation in an industrial environment.
Reliable and robust.
Long-term available (10 years), with 36 months of warranty.



Application-oriented & Customizable

BASE / STYLE / CUSTOM

We are your partner in the complete solution process of industrial computer technology.

From sensor application to tool monitoring in the machine and from embedded computing systems to a future-oriented IIoT gateway concept we represent all product steps with our product brands Prime Cube® and BK Mikro®. At our headquarters in Neuhausen ob Eck (Baden-Württemberg) our 170 employees develop and manufacture customized computer systems: from hardware and software to assemblies and complete systems - innovative force "Made in Germany".

Schubert System Elektronik GmbH

take-off Gewerbepark 36, D-78579 Neuhausen ob Eck

Tel. +49 (0) 7467 9497-0

www.schubert-system-elektronik.de

info@schubert-system-elektronik.de

PRIME PANEL TOUCH ATTACHMENT 15.6" / 21.5"

TECHNICAL DATA

prime
cube®

DESIGN		PRIME PANEL TOUCH ATTACHMENT	
		15.6"	21.5"
Model Code		PPT1000AD_156	PPT1000AD_215
Dimensions (WxHxD)		406.5 x 256 x 73.3 mm	538.6 x 329.5 x 73.3 mm
Weight		5.71 kg	7.90 kg
Housing		Aluminum front frame, powder-coated Aluminum rear panel, powder-coated Aluminum computer core with heat sink, anodized Hardened and anti-glare etched front glass Designed for mounting on a support arm system or VESA mount	
Impact Resistance Front		IK08	
Protection Class*		IP65 acc. EN 60529 all around	
Display	Size	FHD display, 1920 x 1080 pixel, 16:9	
	Luminance (typ.)	450 cd/m²	350 cd/m²
	Contrast Ratio (typ.)	800	1000
	Viewing Angle (typ.)	85/85/85/85°	89/89/89/89°
	Lifetime Lighting (min.)	50,000 h	50,000 h
Touch		Projected Capacitive Touch (PCT), 4-finger operation, up to 10-finger operation optional Specific parameterization possible inhouse	
Interfaces		Display Port (Standard 1.2a)	
		DVI-D 1.0 (DVI-I jack)	
		USB-Hub - 2x USB2.0 (USB-A jack), optional	
Power Consumption		1.17 A / 28.08 W	1.1 A / 26.4 W
Voltage Supply		24 V DC (20,8 ... 28,8 V DC), internal line filter	
Overvoltage Category		II	
Ambient Temperature		-10 °C ... +50 °C	
Storage Temperature		-20 °C ... +65 °C	
Humidity		20% ... 80%, non-condensing	
Operating Altitude		max. 2000 m	
Pollution Degree		2	
EMC Immunity		Industrial area acc. EN 61000-6-2	
EMC Emission		Industrial area acc. EN 61000-6-4	
Shock		Acc. EN/IEC 60721-3-2, Klasse 2M2	
Vibration		Acc. EN/IEC 60721-3-2, Klasse 2M2	
Warranty		36 months	
Approvals		CE; UL in testing; acc. UL 61010-2-201 & CSA C22.2 no. 61010-2-201	

* not evaluated by UL.


Please find dimensional drawings as downloads on our [website](https://www.schubert-system-elektronik.de). 3D-models on request via e-mail to vertrieb@schubert-system-elektronik.de.

Version 1.01 / 2024 © Schubert System Elektronik GmbH. All rights and modifications reserved. All data are non-binding and do not ensure any properties. Pictures/representations may also include special equipment or accessories. We assume no liability for printing errors. The company names, names and logos used are largely protected by copyright and/or trademarks, even if not explicitly marked as such. All product names used are brand names and/or trademarks of the respective manufacturers.

PRIME PANEL TOUCH ATTACHMENT 15.6" / 21.5"

CIRCUIT DIAGRAM

prime
cube®



Please find dimensional drawings as downloads on our [website](https://www.schubert-system-elektronik.de). 3D-models on request via e-mail to vertrieb@schubert-system-elektronik.de.

Version 1.01 / 2024 © Schubert System Elektronik GmbH. All rights and modifications reserved. All data are non-binding and do not ensure any properties. Pictures/representations may also include special equipment or accessories. We assume no liability for printing errors. The company names, names and logos used are largely protected by copyright and/or trademarks, even if not explicitly marked as such. All product names used are brand names and/or trademarks of the respective manufacturers.