

LNx-2602G-SFP Series

26-Port Industrial 1U 19 Inch Rackmount Gigabit PoE+ Unmanaged Ethernet Switch, 24*10/100/1000TX and 2*Gigabit Combo Ports (2*10/100/1000Tx RJ45 and 2*100/1000 SFP Slots)

FEATURES

- ▶ Support 24*10/100/1000Tx RJ45 Ports
- ▶ Support 2*Gigabit Combo Ports (2*10/100/1000Tx RJ45 and 2*100/1000 SFP Slots)
- ▶ 9.6Kbytes Jumbo Frame Support
- ▶ Store-and-Forward Switching Architecture
- ▶ Power Input: 100~240VAC
- ▶ Built-in Relay Output Warning for Power Failure
- ▶ IP40 Protection
- ▶ 1U 19" Rack Mountable
- ▶ Operating Temperature - STD: -10°C to 65°C, EOT: -40°C to 75°C
- ▶ 5-Year Warranty




INTRODUCTION

Antaira Technologies' LNX-2602G-SFP Series is a 26-port industrial Gigabit unmanaged Ethernet switch embedded with 24*10/100/1000Tx Ethernet ports and two gigabit combo ports with 2*10/100/1000 RJ45 ports and 2*100/1000 dual rate SFP slot for fiber connection.

The LNX-2602G-SFP series is IP40 rated and 1U 19" rack mountable. There are also two wide-operating temperature models for either a standard temperature range (STD: -10°C to 65°C) or an extended temperature range (EOT: -40°C to 75°C). It also provides high EFT and ESD protection for industrial networking applications, such as power/utility, water wastewater, oil/gas/mining, factory automation, security surveillance, ITS, and any other outdoor or harsh environment.

DIMENSIONS



SPECIFICATIONS

TECHNOLOGY		MECHANICAL CHARACTERISTICS	
Standards	IEEE 802.3 10Base-T Ethernet	Housing	Metal, IP40 protection
	IEEE 802.3u 100Base-TX Fast Ethernet	Dimension	440 x 44 x 200 mm (W x H x D)
	IEEE 802.3ab 1000Base-T Gigabit Ethernet	Weight	Unit: 5.87 lbs Shipping: 7.71 lbs
	IEEE 802.3z 1000Base-X Gigabit Fiber	Mounting	1U 19" Rackmount
SWITCH PROPERTIES		POWER REQUIREMENT	
Switch Architecture	Switching Fabric (Back-Plane): 52Gbps	Input Voltage	100-240VAC, 50-60Hz
Processing Type	Store and Forward	Power Connection	1 AC socket
Flow Control	IEEE 802.3x flow control, back pressure flow control	Overload Current Protection	Present
Protocol	CSMA/CD	System Power Consumption	21 Watts
Transfer Rate	14,880pps for Ethernet 148,800pps for Fast Ethernet 1,488,000pps for Gigabit Ethernet	ENVIRONMENTAL LIMITS	
MAC Table Size	8K	Operating Temperature	STD: -10°C to 65°C EOT: -40°C to 75°C
Jumbo Frame	9.6Kbytes	Storage Temperature	-40°C ~ 85°C
Memory Buffer	4Mbits	Ambient Relative Humidity	5 to 95%, (non-condensing)
PORT INTERFACE		REGULATORY APPROVALS	
Ethernet Port	24*10/100/1000Base-TX Auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	EMI	FCC Part 15 Subpart B Class A, CE EN61000-6-4 Class A
Gigabit Combo Port	2*10/100/1000Tx RJ45 Ports and 2*100/1000 SFP Slots	EMS	CE EN61000-6-2 Class A, IEC61000-4-2,3,4,5,6,8
LED Indicators	System: Power Ethernet ports: Speed/Link/Active SFP: Speed/Link/Active	Certifications	FCC, CE
Wavelength	Refer to SFP module	Warranty	5 Years
Network Cable	10BaseT: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) 100BaseTX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m) 1000BaseTX: 4-pair UTP/STP Cat. 5/5E cable; EIA/TIA-568 100-ohm (100m)		

ORDERING INFORMATION

LNx-2602G-SFP	26-Port Industrial 1U 19 Inch Rackmount Gigabit Unmanaged Ethernet Switch, 24*10/100/1000TX and 2*Gigabit Combo Ports (2*10/100/1000Tx RJ45 and 2*100/1000 SFP Slots)
LNx-2602G-SFP-T	26-Port Industrial 1U 19 Inch Rackmount Gigabit Unmanaged Ethernet Switch, 24*10/100/1000TX and 2*Gigabit Combo Ports (2*10/100/1000Tx RJ45 and 2*100/1000 SFP Slots); EOT: -40°C to 75°C