

APPC 0760-A01

7" LCD 16:9 Flush Panel PC with Intel® Processor N97,
Multi-Touch Screen, 8G DDR5, 1 x COM, 2 x USB, 1 x USB-C



Main Features

- ♦ 16:9 7" WSVGA fanless LED panel computer
- ♦ Intel® Processor N97
- ♦ 10 points P-Cap multi-touch with zero bezel flush front design
- ♦ 1 x DDR5 SO-DIMM socket
- ♦ Dual Intel® 2.5GbE LAN ports, 2 x USB 3.2, 1 x Line out
- ♦ 1 x RS-232/422/485 with auto flow control, 3 x M.2
- ♦ IP65 compliant front panel
- ♦ Mounting support: panel/wall/stand/VESA 75mm x 75mm
- ♦ DC power input 24V DC

Product Overview

The new 7-inch WSVGA fanless panel PC APPC 0760-A01, featuring an industrial motherboard, is designed for versatile industrial applications. APPC 0760-A01 supports 1024 x 600 (WSVGA) resolution and 500 cd/m2 brightness. Its front panel, with a zero bezel flush front design, complies with the IP65 standard, making it well-suited for industrial environments.

APPC 0760-A01 includes dual 2.5 Gigabit Ethernet connectors, two of M.2 slots support multiple networks, including LAN, WLAN, Wi-Fi and WWAN (5G), as well as various storage options. Additionally, APPC 0760-A01 can also connect to a second display via HDMI®. One adjustable RS-232/422/485 port is also available. APPC 0760-A01 is an ideal choice for general industrial equipment integration.

Specifications

Panel

- ♦ LCD size: 7", 16:9
- ♦ Resolution: WSVGA 1024 x 600
- ♦ Luminance: 500cd/m²
- ♦ Contrast ratio: 800:1
- ♦ LCD Color: 16.7M
- ♦ Viewing angle: 80 (U), 80 (D), 80 (L), 80 (R)
- ♦ Backlight: LED

Touch

- ♦ Ten points P-Cap (projected capacitive touch)
- ♦ Touch light transmission: 85%
- ♦ Anti-scratch surface: 7H hardness
- ♦ Touch interface: USB

Processor

- ♦ Intel® processor N97

Memory

- ♦ 1 x DDR5 SO-DIMM, non-ECC, up to 16GB

Storage

- ♦ 1 x M.2 Key B 2242 SSD (SATA 3.0)

System Capabilities

- ♦ AMI BIOS
- ♦ TPM 2.0


I/O Interface Rear

- ♦ Power button
- ♦ 24V DC input with 3 pins terminal block
- ♦ 2 x USB 3.2, Type-A
- ♦ 1 x HDMI®, up to 4K@30Hz
- ♦ 1 x USB 3.2, Gen 1, Type-C
- ♦ 1 x COM port (DB9), supports RS-232/422/485 auto flow control
- ♦ 1 x Line out
- ♦ 2 x 2.5GbE RJ45 port, Intel® I226-IT
 - Support WoL and PXE
- ♦ 1 x Line out
 - HD audio codec: REALTEK ALC888S-VD

I/O Interface Internal

- ♦ 1 x Key B M.2 2230/3042/3052 (PCIe x1, USB 3.2/ 2.0) for 5G/LTE
- ♦ 1 x Key B M.2 2242 for SATA SSD
- ♦ 1 x Key E M.2 2230/3052 for Wi-Fi
- ♦ 1 x microSD card slot
- ♦ 1 x nano-SIM card slot onboard

Dimension Drawing



Mechanical

- Color: Pantone Black Silver
- IP protection: IP65 front
- Mounting: panel/wall/stand/VESA 75mm x 75mm
- Dimension: 198.4mm x 138.9mm x 62.2mm
- Weight: 1.6kg

Power Supply

- DC 24V $\pm$ 20% input
 - AT and ATX (default) power mode
 - Optional AC to DC power adapter (24V DC, 60W)

Environment

- Vibration:
 - 2G@sine, 5~500Hz, 1hr/axis, IEC 60068-2-64
 - 2Grms@random condition, 5~500Hz, 0.5hr/axis, IEC 60068-2-64
- Shock:
 - 20G@wall mount, half sine, 11ms, IEC 60068-2-27
- Temperature:
 - Operating temperature: -10°C~60° (Ambient with air flow)
 - Storage temperature: -20°C~75°C
- Operating humidity: 10% ~90%, non-condensing,
 - limits to be at 90% RH at max 50°C

Certifications

- CE approval (EN 55032, EN 55035)
- FCC Class A

Operating System

- Windows 11
- Windows 10, 64bit
- Linux

Ordering Information

Barebone

- **APPC 0760-A01 (P/N: 10IA0760001XE)**
7" WSVGA LED backlight touch panel PC, Intel® Processor N97, 8GB DDR5, 1 x COM, 2 x USB, 1 x USB-C

Options

- **24V, 60W AC/DC power adapter w/o power cord (P/N:7400060054X00)**